

Olympic

Description:

The Olympic Barrier offers the complete versatile system for utility and construction applications with hinged side wings designed to rotate and self lock at every 90°. This unique feature allows contractors to create configurations to protect temporary pathway excavations and road works of all kinds.

Features:

- Side wings fold - Easy transport where space is limited.
- Side wings rotate and lock at 90°.
- Fixing area for courtesy board.
- Sliding linking clips to extend barrier.
- Feet can swivel 360°.
- Available in various colours.
- Side wings can be used as door access.

Standards:

- Conforms to requirements of **BSEN8442**
- Reflectivity requirements of **BSEN12899-1**
- Chapter 8 - The Traffic Signs Manual
- The Red Book 2013
- Traffic Signs Regulations & General Directions



Boxed



Wings Open



Anti-Trip Feet



Height:

Width:

Depth:

Weight:

1020 mm

2000 mm or 1250 mm

50 mm

10.00 kg Anti-Trip Foot

11.40 kg Standard Foot

15.40 Kg Tuff-AT Foot

15.80 kg Tuff Foot

**All weights are approximate*

The information given on these sheets is typical of the product depicted it must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice. All measurements are in millimetres (mm)

REMA



FM 673547