

Tuff Barrier

Description:

The Tuff Barrier is a stylish, tough and durable barrier. Incorporating the Q-Clip, the barriers connect together in a linear row. When combined with the Cross-Trench support, the barriers become highly wind resistant.

Features:

- Manufactured from virgin HDPE.
- 600 x 450 sign facility.
- Moulded in orange as standard, but can be coloured to suit.
- When combined with Cross-Trench Support, the stability is greatly improved, and has extremely good resistance to high winds.
- Q-Clip for barrier to barrier connection.
- Barrier may be coloured.
- Compatible with Master barrier.
- Customer identification can be embossed.

Standards:

- Conforms to requirements of **BSEN8442**
- Reflectivity requirements of **BSEN12899-1**
- Chapter 8 - The Traffic Signs Manual
- The Red Book 2013
- Traffic Signs Regulations & General Directions



Cross-Trench



Tuff-AT Foot



Tuff Foot



Height:
Width:
Depth:
Weight:

1000 mm
2000 mm
50 mm
09.10 kg Anti-Trip Foot
10.50 kg Standard Foot
14.50 kg Tuff-AT Foot
14.90 kg Tuff Foot

**All weights are approximate*

The information given on these sheets is typical of the product depicted it must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice. All measurements are in millimetres (mm)

REMA



FM 673547